

### **Amendments to the Claims**

This listing of claims will replace all prior versions and listings of claims in the application:

#### **Listing of Claims:**

1. (Currently amended) A filter structure for filtering air in a gas turbine intake system, the turbine operating at a temperature of about 140°F to 350°F, the intake air having an ambient temperature and a humidity of at least 50% RH, the structure comprising, in an air intake of a gas turbine system, at least one filter element, the filter element having a media pack forming a tubular construction ~~and construction~~ defining an open filter interior; the open filter interior being a clean air plenum, the media pack including a pleated construction of a media composite, the media composite including a substrate at least partially covered by a layer of fine fibers, the fine fibers comprising a polymeric composition comprising an addition polymer or a condensation polymer other than a copolymer formed from a cyclic lactam and a C<sub>6-10</sub> diamine monomer or a C<sub>6-10</sub> diacid monomer combined with an additive material.

2. (Original) The structure of claim 1 wherein the substrate comprises a cellulosic fiber, a synthetic fiber or mixtures thereof.

3. (Currently amended) The structure of claim 1 wherein the additive comprises an oligomer having a molecular weight of about 500 to 3000 and an aromatic character free of an alkyl moiety wherein the additive is miscible in the condensation polymer; ~~and comprising the step of directing the air through the media pack of the filter element and into the open filter interior to clean the air.~~

4. (Original) The structure of claim 1 wherein the polymer comprises a polyalkylene terephthalate.

5. (Original) The structure of claim 1 wherein the polymer comprises a polyalkylene naphthalate.

6. (Original) The structure of claim 1 wherein the polymer comprises a polyethylene terephthalate.

7. (Currently amended) The structure of claim 1 wherein the polymer comprises a nylon ~~polymer~~ copolymer.

8. (Currently amended) The structure of claim 7 wherein the nylon copolymer is combined with a second nylon polymer, the second nylon polymer differing in molecular weight or monomer composition.

9. (Original) The structure of claim 8 wherein the nylon copolymer is combined with a second nylon polymer, the second nylon polymer comprising an alkoxy alkyl modified polyamide.

10. (Original) The structure of claim 8 wherein the second nylon polymer comprises a nylon copolymer.


11. (Original) The structure of claim 8 wherein the polymers are treated to form a single polymeric composition as measured by a differential scanning calorimeter showing a single-phase material.

12. (Original) The structure of claim 11 wherein the copolymer and the second polymer are heat-treated.

13. (Original) The structure of claim 12 wherein the copolymer and the second polymer are heat-treated to a temperature less than the lower melting point of the polymers.


14. (Original) The structure of claim 1 wherein the additive comprises an oligomer comprising tertiary butyl phenol.

15. (Original) The structure of claim 14 wherein the additive comprises an oligomer comprising:




16. (Currently amended) The structure of claim 1 wherein the ~~resin~~ additive comprises an oligomer comprising bis-phenol A.

17. (Original) The structure of claim 16 wherein the additive comprises an oligomer comprising:



18. (Original) The structure of claim 1 wherein the additive comprises an oligomer comprising dihydroxy biphenyl.

19. (Original) The structure of claim 18 wherein the additive comprises an oligomer comprising:



20. (Currently amended) The structure of ~~claim 1~~ claim 3 wherein the additive comprises a blend of the ~~resinous additive~~ oligomer and a fluoropolymer.

21. (Original) The structure of claim 1 wherein the additive comprises a fluorocarbon surfactant.

22. (Original) The structure of claim 1 wherein the additive comprises a nonionic surfactant.

23. (Original) The structure of claim 1 wherein the condensation polymer comprises a polyurethane polymer.

24. (Original) The structure of claim 1 wherein the condensation polymer comprises a blend of a polyurethane polymer and a polyamide polymer.

25. (Original) The structure of claim 24 wherein the polyamide polymer comprises a nylon.

26. (Original) The structure of claim 25 wherein the nylon comprises a nylon homopolymer, a nylon copolymer or mixtures thereof.

27. (Original) The structure of claim 1 wherein the condensation polymer comprises an aromatic polyamide.

28. (Original) The structure of claim 1 wherein the condensation polymer comprises a reaction product of a diamine monomer and poly(m-phenylene isophthalamide).

29. (Original) The structure of claim ~~28~~ 27 wherein the polyamide comprises a reaction product of a diamine and a poly(p-phenylene terephthalamide).

30. (Original) The structure of claim 1 wherein the condensation polymer comprises a polybenzimidazole.

31. (Original) The structure of claim 1 wherein the condensation polymer comprises a polyarylate.

32. (Original) The structure of claim 31 wherein the polyarylate polymer comprises a condensation polymerization reaction product between bis-phenol-A and mixed phthalic acids.

33. (Currently amended) A method for filtering air in a gas turbine intake system, the turbine operating at a temperature of about 140°F to 350°F, the intake air having an ambient temperature and a humidity of at least 50% RH, the method comprising the steps of:

(a) installing a filter proximate an air intake of a gas turbine system, the filter comprising at least one filter element, the filter element having a media pack forming a tubular construction ~~and construction~~ defining an open filter interior; the open filter interior being a clean air plenum, the media pack including a pleated construction of a media composite, the media composite including a substrate at least partially covered by a layer of fine fibers, the fine fibers comprising a polymeric composition comprising an addition polymer or a condensation polymer other than a copolymer formed from a cyclic

lactam and a C<sub>6-10</sub> diamine monomer or a C<sub>6-10</sub> diacid monomer combined with an additive material; and

(b) directing intake air into an air intake of a gas turbine ~~system~~ system.

34. (Original) The method of claim 33 wherein the additive comprises an oligomer having a molecular weight of about 500 to 3000 and an aromatic character free of an alkyl phenolic moiety wherein the additive is miscible in the condensation polymer; and comprising the step of directing the air through the media pack of the filter element and into the open filter interior to clean the air.

35. (Currently amended) The ~~composition~~ method of claim 33 wherein the polymer comprises a polyalkylene terephthalate.

36. (Currently amended) The ~~composition~~ method of claim 33 wherein the polymer comprises a polyalkylene naphthalate.

37. (Currently amended) The ~~composition~~ method of claim 33 wherein the polymer comprises a polyethylene terephthalate.

38. (Currently amended) The ~~composition~~ method of claim 33 wherein the polymer comprises a nylon polymer.

39. (Currently amended) The ~~composition~~ method of claim ~~33~~ 38 wherein the nylon copolymer is combined with a second nylon polymer, the second nylon polymer differing in molecular weight or monomer composition.

40. (Currently amended) The ~~composition~~ method of claim 33 wherein the nylon copolymer is combined with a second nylon polymer, the second nylon polymer comprising an alkoxy alkyl modified polyamide.

41. (Currently amended) The composition method of claim 39 wherein the second nylon polymer comprises a nylon copolymer.


42. (Currently amended) The composition method of claim 39 wherein the polymers are treated to form a single polymeric composition as measured by a differential scanning calorimeter showing a single-phase material.

43. (Currently amended) The composition method of claim 42 wherein the copolymer and the second polymer are heat-treated.

44. (Currently amended) The composition method of claim 43 wherein the copolymer and the second polymer are heat-treated to a temperature less than the lower melting point of the polymers.


45. (Currently amended) The composition method of claim + 33 wherein the additive comprises an oligomer comprising tertiary butyl phenol.

46. (Currently amended) The composition method of claim 45 wherein the additive comprises an oligomer comprising:




47. (Currently amended) The composition method of claim 33 wherein the resin additive comprises an oligomer comprising bis-phenol A.

48. (Currently amended) The ~~composition method~~ of claim 47 wherein the additive comprises an oligomer comprising:



49. (Currently amended) The ~~composition method~~ of claim 33 wherein the ~~resin~~ additive comprises an oligomer comprising dihydroxy biphenyl.

50. (Original) The composition of claim 49 wherein the additive comprises an oligomer comprising:



51. (Currently amended) The ~~composition method of claim 33~~ composition method of claim 34 wherein the additive comprises a blend of the ~~resinous-additive oligomer~~ and a fluoropolymer.



52. (Currently amended) The ~~composition~~ method of claim 33 wherein the additive comprises a fluorocarbon surfactant.

53. (Currently amended) The ~~composition~~ method of claim 33 wherein the additive comprises a nonionic surfactant.

54. (Currently amended) The ~~composition~~ method of claim 33 wherein the condensation polymer comprises a polyurethane polymer.

55. (Currently amended) The ~~composition~~ method of claim 33 wherein the condensation polymer comprises a blend of a polyurethane polymer and a polyamide polymer.

56. (Currently amended) The ~~composition~~ method of claim 55 wherein the polyamide polymer comprises a nylon.

57. (Currently amended) The ~~composition~~ method of claim 56 wherein the nylon comprises a nylon homopolymer, a nylon copolymer or mixtures thereof.

58. (Currently amended) The ~~composition~~ method of claim 33 wherein the condensation polymer comprises an aromatic polyamide.

59. (Currently amended) The ~~composition~~ method of claim 33 wherein the condensation polymer comprises a reaction product of a diamine monomer and poly(m-phenylene isophthalamide).

60. (Currently amended) The ~~composition~~ method of claim 58 wherein the polyamide comprises a reaction product of a diamine and a poly(p-phenylene terephthalamide).

61. (Currently amended) The ~~composition~~ method of claim 33 wherein the condensation polymer comprises a polybenzimidazole.

62. (Currently amended) The ~~composition~~ method of claim 33 wherein the condensation polymer comprises a polyarylate.

63. (Currently amended) The ~~composition~~ method of ~~claim 29~~ claim 62 wherein the polyarylate polymer comprises a condensation polymerization reaction product between bis-phenol-A and mixed phthalic acids.

64. (Original) The method according to claim 33 wherein, said step of directing air into an air intake of a gas turbine system having at least one filter element includes directing air into an air intake of a gas turbine system having a plurality of filter element pairs, each of the filter element pairs including a first tubular filter element with the media pack sealed against an end of a second tubular filter element with the media pack; each of the first and second tubular filter elements defining the clean air plenum.

65. (Currently amended) A method according to ~~claim 33~~ claim 64 wherein said step of directing air into an air intake of a gas turbine system having a plurality of filter element pairs includes directing air into the first tubular filter element and the second tubular filter element; wherein the first tubular filter element is cylindrical and the second tubular filter element is conical.

66. (Currently amended) A method according to ~~claim 33~~ claim 64 further including directing a pulse of air into each of the clean air plenums of each of the filter element pairs to at least partially remove particulates collected on each of the media packs.

67. (Original) A method for filtering air in a gas turbine intake system, the method comprising, in a turbine operating at a temperature of about 140°F to 350°F, an intake air having an ambient temperature and a humidity of at least 50% RH,

(a) directing intake air into an air intake of a gas turbine system having at least one filter element, the filter element having a media pack forming a tubular construction and construction defining an open filter interior; the open filter interior being a clean air plenum, the media pack including a pleated construction of a media composite, the

media composite including a substrate at least partially covered by a layer of fine fibers, the fine fibers comprising a condensation polymer, other than a copolymer formed from a cyclic lactam and a C<sub>6-10</sub> diamine monomer or a C<sub>6-10</sub> diacid monomer, and a resinous additive comprising an oligomer having a molecular weight of about 500 to 3000 and an aromatic character wherein the additive is miscible in the condensation polymer; and

(b) directing the air through the media pack of the filter element and into the open filter interior to clean the air.

68. (Currently amended) The ~~composition~~ method of claim 67 wherein the condensation polymer comprises a polyalkylene terephthalate.

69. (Currently amended) The ~~composition~~ method of claim 67 wherein the condensation polymer comprises a polyalkylene naphthalate.

70. (Currently amended) The ~~composition~~ method of claim 67 wherein the condensation polymer comprises a polyethylene terephthalate.

71. (Currently amended) The ~~composition~~ method of claim 67 wherein the condensation polymer comprises a nylon polymer comprising a homopolymer having repeating units derived from a cyclic lactam.

72. (Currently amended) The ~~composition method of claim 67~~ claim 71 wherein the nylon ~~copolymer~~ polymer is combined with a second nylon polymer, the second nylon polymer differing in molecular weight or monomer composition.

73. (Currently amended) The ~~composition method of claim 67~~ claim 71 wherein the nylon ~~copolymer~~ polymer is combined with a second nylon polymer, the second nylon polymer comprising an alkoxy alkyl modified polyamide.

74. (Currently amended) The ~~composition~~ method of claim 73 wherein the second nylon polymer comprises a nylon copolymer.


75. (Currently amended) The ~~composition~~ method of claim 73 wherein the polymers are treated to form a single polymeric composition as measured by a differential scanning calorimeter showing a single phase material.

76. (Currently amended) The ~~composition~~ method of claim 74 wherein the copolymer and the second polymer are heat treated.

77. (Currently amended) The ~~composition~~ method of claim 74 wherein the copolymer and the second polymer are heat treated to a temperature less than the lower melting point of the polymers.


78. (Currently amended) The ~~composition~~ method of claim 67 wherein the additive comprises an oligomer comprising tertiary butyl phenol.

79. (Currently amended) The ~~composition~~ method of claim 78 wherein the additive comprises an oligomer comprising:




80. (Currently amended) The ~~composition~~ method of claim 67 wherein the ~~resin~~ additive comprises an oligomer comprising bis-phenol A.

81. (Currently amended) The composition method of claim 80 wherein the additive comprises an oligomer comprising:



82. (Currently amended) The composition method of claim 67 wherein the resin additive comprises an oligomer comprising dihydroxy biphenyl.

83. (Currently amended) The composition method of claim 82 wherein the additive comprises an oligomer comprising:



84. (Currently amended) The composition method of ~~claim 67~~ claim 78 wherein the additive comprises a blend of the ~~resinous additive oligomer~~ and a fluoropolymer.

85. (Currently amended) The ~~composition~~ method of claim 67 wherein the additive comprises a fluorocarbon surfactant.

86. (Currently amended) The ~~composition~~ method of claim 67 wherein the additive comprises a nonionic surfactant.

87. (Currently amended) The ~~composition~~ method of claim 67 wherein the condensation polymer comprises a polyurethane polymer.

88. (Currently amended) The ~~composition~~ method of claim 67 wherein the condensation polymer comprises a blend of a polyurethane polymer and a polyamide polymer.

89. (Currently amended) The ~~composition~~ method of claim 88 wherein the polyamide polymer comprises a nylon.

90. (Currently amended) The ~~composition~~ method of claim 89 wherein the nylon comprises a nylon homopolymer, a nylon copolymer or mixtures thereof.

91. (Currently amended) The ~~composition~~ method of claim 67 wherein the condensation polymer comprises an aromatic polyamide.

92. (Currently amended) The ~~composition~~ method of claim 67 wherein the condensation polymer comprises a reaction product of a diamine monomer and poly(m-phenylene isophthalamide).

93. (Currently amended) The ~~composition~~ method of claim 92 wherein the polyamide comprises a reaction product of a diamine and a poly(p-phenylene terephthalamide).

94. (Currently amended) The ~~composition~~ method of claim 67 wherein the condensation polymer comprises a polybenzimidazole.

95. (Currently amended) The ~~composition~~ method of claim 67 wherein the condensation polymer comprises a polyarylate.

96. (Currently amended) The ~~composition~~ method of ~~claim 29~~ claim 95 wherein the polyarylate polymer comprises a condensation polymerization reaction product between bis-phenol-A and mixed phthalic acids.

97. (Original) The method according to claim 67 wherein, said step of directing air into an air intake of a gas turbine system having at least one filter element includes directing air into an air intake of a gas turbine system having a plurality of filter element pairs, each of the filter element pairs including a first tubular filter element with the media pack sealed against an end of a second tubular filter element with the media pack; each of the first and second tubular filter elements defining the clean air plenum.

98. (Currently amended) A method according to ~~claim 67~~ claim 97 wherein said step of directing air into an air intake of a gas turbine system having a plurality of filter element pairs includes directing air into the first tubular filter element and the second tubular filter element; wherein the first tubular filter element is cylindrical and the second tubular filter element is conical.

99. (Currently amended) A method according to ~~claim 67~~ claim 98 further including directing a pulse of air into each of the clean air plenums of each of the filter element pairs to at least partially remove particulates collected on each of the media packs.